



## **FLEXIBLE AND FAST INSTALLATION ALSO IN REMOTE AREAS: DEEP DRILLING RIG TERRA INVADER 350/450 SLINGSHOT.**

- ▶ Slingshot substructure and self-erecting telescoping mast allow easy and safe rig up
- ▶ Push and pull capability
- ▶ Semi-automatic pipe handling system (hands-off-technology)
- ▶ Easy and safe casing operations
- ▶ Sophisticated noise-protection system
- ▶ Made in Germany



## DEEP DRILLING RIG TERRA INVADER 350/450 SLINGSHOT. TECHNICAL SPECIFICATIONS.

### HOOK LOAD

Max. hook load TI-350:	350mt (385sht)
Max. hook load TI-450:	450mt (500sht)

### MAST\*

Type:	telescopic twin profile
Height (erected):	46m (150ft)

### SUBSTRUCTURE\*

Type:	slingshot
Height:	9m (30ft) rig floor plus 3m (10ft) windwalls
Clear height below RT:	8.2m (27ft)
BOP handling:	2x 25mt (2x 28sht)
Rig floor dimensions:	9m x 10m (30ft x 33ft)

### CYLINDER HOISTING SYSTEM

Type:	double cylinder system
Hoist power:	1,600kW (2,200hp)
Brake:	hydraulic lowering brake valves
Stroke:	22m (72ft)

Ultra-sensitive operation due to multi-valve hydraulic control.

### TOP DRIVE\*

Type:	HV TD H 500-1000
Max. static load:	450mt (500sht)
Max. push load:	160mt (175sht)
Max. rotary speed:	220rpm at 31,000Nm (22,800ft-lbs)
Max. continuous rotary torque:	62,000Nm (45,500ft-lbs) at 110rpm
Max. brake torque:	70,000Nm (51,600ft-lbs)
Link tilt capacity:	4mt at 1.5m (8,820lbs at 4.92ft)
Rated power:	800kW (1,000hp)

Including IBOP, pipe handler, integrated swivel with quill and dolly with torque pick-up.

### RIG POWER SUPPLY\*

Hydraulic power unit:	4x 500kW (4x 670hp)
Generator set	
Max. power diesel engine:	1,232kW (1,650hp)
Max. power generator:	1,540kVA
Emergency supply unit	
Emergency power diesel engine:	600kW (800hp)
Emergency power generator:	715kVA
Hydraulic auxiliary unit:	90kW (120hp)
Compressed air power unit:	2x 30kW (2x 40hp)
Power control center	

The rig can be operated with:

- power from the grid
- power from the generator sets
- generator supported grid power

a. and c. require an additional medium voltage switchgear unit.

### AUXILIARY CRANE

Type:	PK 32080 M
Drive:	hydraulic
Lifting moment:	298,000Nm (220,000ft-lbs)
Max. lifting capacity:	8.5mt (10sht)
Slewing angle:	400 degrees

The auxiliary crane mounted on the rig floor can be steered by a wireless remote-control panel and has a maximum reach of 12.2m.

### MUD PUMP UNITS

Make:	Schäfer Et Urbach / Herrenknecht Vertical
Type:	high pressure triplex mud pump
Max. operating pressure:	350 bar to 517 bar (5,000psi to 7,500psi)
Max. input power:	800kW to 1,600kW (1,000hp to 2,200hp)
Drive:	AC or DC (water- or air-cooled)

The mud pump units are tailored to customer requirements.

### DRILLER'S CABIN\*

Controls:	joystick, trackball and touch screen with camera control
-----------	--

### PIPE HANDLING SYSTEM\*

Drive:	hydraulic
Operating range:	73mm (2 7/8") to 620mm (24 1/2")
Lifting capacity:	4.5mt (5sht)
Max. tripping speed:	600m/h (1,920ft/h)

The complete pipe handling system is designed to handle drill pipe range 2 in doubles, drill collars and casing. The controls are semi-automated and the system is operated by the pipe handling operator or the driller.

An integrated anti-collision system ensures a safe pipe handling process during all operations.

### ROTARY TABLE\*

Table opening:	953mm (37 1/2")
Max. static load:	450mt (500sht)
Max. dynamic load:	350mt (385sht)
Drive:	hydraulic

### OPTIONAL EQUIPMENT

- ▶ Iron roughneck / manual rotary tongs
- ▶ Power slips / slip lifter / manual slips
- ▶ Elevators
- ▶ Auxiliary winch
- ▶ BOP / BOP closing unit
- ▶ Medium voltage switchgear unit
- ▶ Mud tank system
- ▶ Drill string

\* Components manufactured by Herrenknecht Vertical

HERRENKNECHT VERTICAL GmbH

Im Heidenwinkel 5

D-77963 Schwanau

Phone +49 7824 302-1300

Fax +49 7824 302-1330

info@vertical-herrenknecht.com

www.herrenknecht-vertical.com

